



Technische Daten

- Einfachwirkend
- Belastet
- Drehrichtungsabhängig
- Kegelfeder

Einsatzgrenzen

d1 = 16 - 100 mm
 p = 10 bar
 t = -50 °C - 200 °C
 vg = 10 m/s

Werkstoffe

Gleitring:	Kohle	(Z32)
	SiC	(U32)
	WC	(K22)
	VA	(E)
Elastomer:	Viton	(V)
	EPDM	(D)
	FEP	(V2)
Andere Bauteile:	Edelstahl	(E)

d ₁	d ₃	l ₃
10	19	15,5
12	21	16,0
14	23	16,5
15	24	18,0
16	26	18,0
18	32	20,0
20	34	23,0
22	36	23,0
24	38	24,0
25	39	27,0
28	42	28,0
30	44	29,0
32	46	30,0
33	47	31,0
35	49	31,0
38	54	37,0
40	56	38,0
43	59	40,0
45	61	44,0
48	64	46,0
50	66	48,0
53	69	49,0
55	71	50,0
58	78	55,0
60	80	55,0
63	83	57,0
65	85	58,0
70	90	58,0
75	98	60,0
80	100	62,0
85	105	62,0
90	110	64,0
95	115	64,0
100	120	65,0

Stand 06/07

Änderungen jederzeit vorbehalten