



Technische Daten

- Einfachwirkend
- Entlastet
- Drehrichtungsunabhängig
- Metallbalg

Einsatzgrenzen

d1 = 20 - 100 mm
 p = 20 bar
 t = -40 °C - 250 °C
 vg = 25 m/s

Werkstoffe

Gleitring: Kohle (Z32)
 SIC (U32)
 Elastomer: Viton (V)
 EPDM (D)
 Metallbalg: AM 350 (P6)
 Andere Bauteile: Edelstahl (E)

d1	d3	l3
20	33,5	30,5
22	36,5	30,5
24	39,0	28,5
25	39,6	28,5
28	42,8	31,0
30	45,0	31,0
32	46,0	31,0
33	48,0	31,0
35	49,2	31,0
38	52,3	31,0
40	55,5	31,0
43	57,5	31,0
45	58,7	31,0
48	61,9	31,0
50	65,0	32,5
53	68,2	32,5
55	70,0	32,5
58	71,7	37,5
60	74,6	37,5
65	84,1	37,5
70	87,3	42,0
75	95,0	42,0
80	98,4	41,8
85	104,7	41,8
90	111,0	46,8
95	114,0	47,8
100	117,4	47,8

Stand 06/07

Änderungen jederzeit vorbehalten