



Technische Daten

- Einfachwirkend
- Entlastet
- Drehrichtungsunabhängig
- Metallrollbalg
- nach EN 12756 (DIN24960)

Einsatzgrenzen

$d_1 = 20 - 100 \text{ mm}$
 $p = 10 \text{ bar}$
 $t = -40 \text{ °C} - 200 \text{ °C}$
 $vg = 20 \text{ m/s}$

Werkstoffe

Gleitring: SIC (U32)
 Elastomer: Viton (V)
 Metallbalg: Edelstahl (E)
 Andere Bauteile: Edelstahl (E)

d_1	d_3	l_3
20	34,0	30,5
22	36,0	30,5
24	38,0	33,0
25	39,0	33,0
28	42,0	35,5
30	44,0	35,5
32	46,0	35,5
33	47,0	35,5
35	49,0	35,5
38	54,0	37,0
40	56,0	37,0
43	59,0	37,0
45	61,0	37,0
48	64,0	37,0
50	66,0	38,0
53	69,0	38,0
55	71,0	38,0
58	78,0	42,0
60	80,0	42,0
65	85,0	42,0
70	90,0	48,5
75	99,0	48,5
80	104,0	48,5
85	109,0	48,5
90	114,0	52,0
95	119,0	52,0
100	124,0	52,0